

Please read these guidelines carefully before installing and using the product.

SAFETY INFORMATION

- Always wear appropriate safety equipment.
- This product requires two people for installation.
- If this product falls down, serious or fatal crushing injuries can occur. This product should be permanently fixed to the wall – contact your local fastening device retailer for advice on what fastening devices are suitable for your walls.
- Assembly should be carried out by an appropriately skilled person, due to the risk of wrongful assembly leading to injury or damage.













TOWER SHELL BO	X					
	• :	:	•	· · ·	o c	
		•	٠	•		
	•				0	16 x cams 20 mm diameter
					1 x deck	20 mm diameter
	*			•	575 mm W x 447 mm H	
					x 16 mm D	*
		•	•			
	:	:	:	:	0 0	16 x cam bolts
2 x drawer tower sides 2000 mm W x 447 mm I	4 x 16 mm D					16 mm H x 6 mm diameter
200011111111111	1 × 101111111					- 🗥
0	0	(0	O	0	
1 x shelf nailer	1 x front to			x nailers	1 x fixed shelf	A
575 mm W x 95 mm H x 16 mm D	575 mm W x 95 mm H x 16mm D			75 mm W x 95 mm H 16 mm D	575 mm W x 447 mm H x 16 mm D	16 x adjustable shelf pins 10 mm W x 14 mm H x 13 mm
TOP SHELF BOX						
TOP SHELF BOX						
TOP SHELF BOX						
TOP SHELF BOX						
TOP SHELF BOX						
1 x top shelf	7 mm H x 16 m	m D				
TOP SHELF BOX 1 x top shelf Up to 3000 mm W x 44	7 mm H x 16 m	m D				
1 x top shelf Up to 3000 mm W x 44	7 mm H x 16 m	m D				
1 x top shelf						
1 x top shelf Up to 3000 mm W x 44						
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95	mm H x 16 mr					
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95	mm H x 16 mr					
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95	mm H x 16 mr					
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95 1 x hanging rail 3000 mm W x 35 mm d	mm H x 16 mr ameter	n D	Ų		4 x hanging rail brackets	1x sharkfin support bracke
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95	mm H x 16 mr	n D) 8 ·	x hanging rail screws	4 x hanging rail brackets 45 mm H	1 x sharkfin support bracke 300 mm W x 300 mm H
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95 1 x hanging rail 3000 mm W x 35 mm d 2 x side cleats 425 mm W x 95 mm H	ameter Fast caps (n D) 8 ·	x hanging rail screws		1 x sharkfin support bracke 300 mm W x 300 mm H
1 x top shelf Up to 3000 mm W x 44 1 x back cleat Up to 3000 mm W x 95 1 x hanging rail 3000 mm W x 35 mm d 2 x side cleats 425 mm W x 95 mm H x 16 mm D	ameter Fast caps (n D) 8 ·	x hanging rail screws		

2 www.stegbar.com.au/support

 $575 \, \text{mmW} \, \text{x} \, 447 \, \text{mmH} \, \text{x} \, 16 \, \text{mmD}$

2 x adjustable shelves



DRAWER RUNNERS BOX




4 x drawer side (left)



4 x drawer side (right)



Drawer Front Fixing Bracket



4 x drawer runner (left)



4 x drawer runner (right)



4 x drawer side cover cap (bottom)



4 x drawer side cover cap (top)



drawer screw #1 6G x 16 mm CSK



drawer screw #4 6G x 10 mm CSK



34 x Euro screw



4 x back fixing bracket (left)



4 x back fixing bracket (right)

BACK, BASES AND FRONT BOX



4 x drawer bases




4 x drawer backs




4 x drawer fronts

HANDLES BOX



4 x drawer handles



Na care

4 x drawer handle bolts 47 mm H x 5 mm diameter

EXTRA ITEMS AND TOOLS REQUIRED CHECKLIST

These items are readily available from all major hardware stores.

Drill and No.2 Phillips head driver	Builder's square
Multi tool	Countersink drill bit
Stepladder	Hammer
Phillips head screwdriver	Liquid Nails
Spirit level	Gapping
Measuring tape and pencil	Packers
Circular saw	6-gauge 40 mm screws
Silicone/caulking gun	6-gauge 13 mm screws
Stud finder	6-gauge 28 mm screws
3 mm drill bits	Wallmates

IMPORTANT BUILDING TERMINOLOGY

In construction, tradespeople use terms like 'square', 'level' and 'plumb' to be sure that their measurements are accurate, and the finished project is successful. Here are some definitions of common building terminologies.

Square: when corners are 90 degrees.

Level: straight from side to side, like a shelf that's been properly installed.

Plumb: straight up and down, like the walls of a building.

Flush: when two adjoining surfaces are perfectly flat next to each other.

Skirting: a board that runs along the border between the interior wall and the floor. **Architrave:** is used to frame windows and openings to conceal any shrinkage or movement

that may occur between the wall and the casing within the door surround.

Jamb: is a flat surface that runs vertically on each side of the door frame.


Scribe: cutting away the waste material that is preventing two materials from meeting

together perfectly.

IMPORTANT INFORMATION


- Pre-drill board and countersink before fixing to walls.
- · Read guidelines carefully before commencing.






Open tower shell box.


Screw in cam bolts into drawer tower sides (both sides).



Hammer cams into nailers, toe, deck and fixed shelf.




Place nailers over cam bolts and tighten.
Place deck over cam bolts and tighten.
Place fixed shelf over cam bolts and tighten.




Place side on top over cam bolts and tighten cams.





Fix runners L (B) and R (H) to tower sides, screwing euro screw into third hole in top row (Exploded image).




Open Drawer, Runners box and Backs bases and fronts box


Layout all parts to assemble drawers

1. Attach back bracket to timber back


7




2. Slide back into draw sides and fix screws



3. Slide drawer base into Runner slot




4. Turn drawer over and fix screws




5. Tap drawer front bracket into pre-drilled holes of drawer front






6. Line drawer front with lots in runner and push in until it clicks



7. Slide out runners position drawer over runner and push all the way in until it clicks

Step 8




Fully extend runner. Place drawer on runner and push drawer all the way in until you hear a click


drawer is now enaged to runner

Drawer Adjustment


1. Move up down at front



2. Move laterally at front





3. tilt drawer up and down at back




4. Fit all cover caps










How to Remove Drawers


- 1. Extend drawer
- 2. Lift drawer vertcially to disenagae from runner

How to Remove Drawer Front

1. Insert screwdrivers and rotate left and right to release lock



Step 9



Check wall for plumb, place level on wall.

If wall greater than 3 mm out of plumb, scribe infill.


TIP: Refer to our guide – How to scribe infill.

All our guides are located at: stegbar.com.au/support

If required, using the 6 x 28 6-gauge screws, screw 16 mm infill to wall side of shelf unit flush with the front.




Step 10




Measure the width and depth of tower and mark skirting with pencil (be sure to include the infill if infill required).

Step 11



Use multi tool to cut and remove skirting where tower to be installed.



Pre-drill 2 x 3 mm holes into tower nailer.


Place tower in position. Place level on tower to ensure level and plumb.

Mark wall with pencil.

Fix 40 mm screw into stud - if stud is not present, then fix with screw and plug (wallmate).


TIP: Use packers to level tower.

TIP: Pre-drill board and countersink.



Use spirit level to mark horizontal line from top of shelf unit across full width of rear wall for back cleat and side cleat positioning.

Locate wall studs with stud finder and mark wall above pencil line (no greater than 16 mm).




Open top shelf box.

Apply liquid nails to back of side cleat in radio wave pattern and screw cleat to wall into stud.

If stud is not present, then fix with screw and plug (wallmate).








Measure distance from tower to side cleat.

Cut back cleat to size.

Apply liquid nails to back of cleat in radio wave pattern and screw cleat to wall into stud.

TIP: Pre-drill board and countersink.




Measure top shelf width ensuring you check the walls are square using a square edge.

Cut top shelf to correct size allowing for wall run outs.

Place top shelf into position screw top shelf down into wall cleats using 40 mm screws.

TIP: Pre-drill board and countersink.






Measure 214 mm off cleat on back wall and 80 mm down from side cleat, thus measurement is to the bottom hole of hanging rod end.

Fix hang rail ends using 16 mm screws.

Repeat on tower side.



Measure distance between board (tower to side cleat) and deduct 6 mm off overall width.

Cut hang rail to size and insert into hanging rail end ends.


TIP: Face top hang rail with groove up.

Step 19


Hanging rail sharkfin support must be screwed into a stud.

Push sharkfin support into wall cleat making sure sharkfin is plumb and square with back cleat.

Screw sharkfin support into back cleat and top shelf with 13 mm screws and 40 mm screw into wall stud.



Using caulking gun, gap all connections between board and wall or board and board.




Open adjustable shelves box.

Install adjustable shelves.

Place shelf pins into tower at desired heights.

Place shelf on pins.





Fast cap (white dot) all screws.

Clean shelving with damp cloth and remove stickers.



Stegbar is not providing any installation of the product, which is your responsibility. The information in this assembly document is of a general nature only and is provided regarding a typical installation process. Accordingly, this assembly document does not take into account your specific circumstances, environment, needs, tools or skills.

You should not rely solely on the general information in this assembly document for installation. There are risks associated with installation and you assume those risks voluntarily by installing this product. To the extent permitted by law, Stegbar does not accept responsibility and is not liable for any loss, damage or injury suffered by you as a result of any circumstances specific to you that are not addressed in these assembly documents.

You should independently consider whether the services of any third party are appropriate for you. Any service supplied by a third party is subject to the terms and conditions of that third party. Stegbar is not responsible for any agreements, maintenance, delivery or satisfaction of any transactions undertaken with a third-party provider. To the extent permitted by law, Stegbar is not responsible is and is not liable for any loss, damage or injury suffered by you as a result of the conduct of the third party.

Stegbar reserves the right to alter or amend without prior notice general information and design details specified in these assembly documents. JWSNAT0573/0423 I stegbar.com.au I Version 1.0 I October 2023